

Model:RS-KJ12

30 CM Subwoofer Speaker



SPECIFICATIONS

General Data		Unit
Overall Dimensions	318x194	mm
Nominal Power Handling	2000	W
Maximum Power	4000	W
Sensitivity	84.3	db
Frequency Response	35-500	Hz
Cone Material	Non Pressed Paper Cone	
Basket	Aluminium	
Net Weight	10	kg
Electrical Data		
Nominal Impedance	2X2/2X4	ohm
DC Resistance	2X1.8/2X3.6	ohm
Voice Coil and Magnet Parameters		
Voice Coil Diameter	76.5	mm
Voice Coil Height	38	mm
HE magnetic Gap Height	14	mm
Voice Coil bobbin	AL	
Number of Layers	4L	
Magnet System Type	Ferrite	
T-S Parameters		
Suspension Compliance	61.01/71.2	Cms
Mechanical Q Factor	5.1/4.8	Qms
Electrical Q Factor	0.62/0.64	Qes
Total Q Factor	0.55/0.27	Qts
Moving Mass	303/295	Mms
Eq.Cas AIR Load	21.5/20.1	Vas
Resonant Frequency	37/38.2	Fs
Effective Piston Area	498cm ²	SD

FEATURES
* Aluminium Basket
* Non Pressed Paper Cone With Treated Foam Surround
* High Temperature 3.0" Voice Coil
* Ferrite Magnet Structre

Dimensions

