

20 CM 2 Way Coaxial Midrange Speaker



SPECIFICATIONS

General Data			Unit	FEATURES	
Overall Dimensions	Ø215 x 94	mm		Steel Basket	
Nominal Power Handling	250	W		Pressed Paper Cone, Treated Cloth Surround	
Maximum Power	500	W		High Temperature CCAW Voice Coil	
Sensitivity	97	dB		Ferrite Magnet Structure	
Frequency Response	75~20000	Hz		Tweeter: 1" CCAW Voice Coil, Aluminium Diaphragm	
Cone Material	Pressed Paper			Dimensions	
Basket	Steel				
Net Weight	3.56	kg			
Electrical Data					
Nominal Impedance	4	Ohm			
DC Resistance	3.2	Ohm			
Voice Coil and Magnet Parameters					
Voice Coil Diameter	44.7	mm			
Voice Coil Height	10	mm			
Magnetic Gap Height	6	mm			
Voice Coil Robbin	TIL				
Number of Layers	2L				
T-S Parameters					
Suspension Compliance	217.682µM/N	Cms			
Mechanical Q Factor	7.56	Qms			
Electrical Q Factor	0.287	Qes			
Total Q Factor	0.276	Qts			
Moving Mass	21.076g	Mms			
Eq. Cas AIR Loaded	20.671L	Vas			
Resonant Frequency	74.304Hz	Fs			

Effective Piston Area	258.60cm ²	SD	
-----------------------	-----------------------	----	--