

Model:RS-KM12

30 CM Subwoofer Speaker



SPECIFICATIONS

General Data		Unit
Overall Dimensions	329x173	mm
Nominal Power Handling	1500	W
Maximum Power	3000	W
Sensitivity	84	db
Frequency Response	35-500	Hz
Cone Material	Non Pressed Paper Cone	
Basket	Aluminium	
Net Weight	12	kg
Electrical Data		
Nominal Impedance	2X2/2X4	ohm
DC Resistance	2X1.8/2X3.6	ohm
Voice Coil and Magnet Parameters		
Voice Coil Diameter	76.5	mm
Voice Coil Height	55	mm
HE magnetic Gap Height	16	mm
Voice Coil bobbin	AL	
Number of Layers	4L	
Magnet System Type	Ferrite	
T-S Parameters		
Suspension Compliance	63/65.7	Cms
Mechanical Q Factor	2.68/2.35	Qms
Electrical Q Factor	0.53/0.58	Qes
Total Q Factor	0.44/0.49	Qts
Moving Mass	318/305	Mms
Eq.Cas AIR Load	21.6/20.2	Vas
Resonant Frequency	35.5/36.3	Fs
Effective Piston Area	491cm ²	SD
Xmax	19.5mm	

FEATURES

- * Aluminium Basket
- * Non Pressed Paper Cone With Treated Foam Surround
- * High Temperature 3.0" Voice Coil
- * Ferrite Magnet Structre

Dimensions

