

General Data			Unit	Features
Overall Dimensions	204*83.3		mm	20 CM MIDRANGE SPEAKER
Nominal Power Handling	130		W	BLACK PAPER CONE WITH CLOTH EDGE
Maximum Power	260		W	IMPEDANCE: 4 Ω
Sensitivity	93		dB	RATED POWER: 130W
Frequency Response	90-15K		Hz	MAX. POWER: 260W
Cone Material	PAPER CONE			FREQUENCY RESPONSE: 90-15KHZ
Basket	METAL			SENSITIVITY: 92DB
Net Weight	1,06		kg	Dimensions
Electrical Data				
Nominal Impedance	4		Ohm	
DC Resistance	3,2		Ohm	
Voice Coil and Magnet Parameters				
Voice Coil Diameter	Φ25.5		mm	
Voice coil wire	CCA W			
Voice Coil Height	6		mm	
Magnetic Gap Height	4		mm	
Magnet system type	High Flux Ferrite			
Voice Coil Bobbin	KAPTON			
Number of Layers	2L			
T-S Parameters				
Suspension Compliance	0,2550		Cms	
Mechanical Q Factor	11,58		Qms	
Electrical Q Factor	1,85		Qes	
Total Q Factor	1,59		Qts	
Moving Mass	10,9573		Mms	
Eq. Cas AIR Loaded	16,2795		Vas	
Resonant Frequency	100		Fs	
Effective Piston Area	2,14E+02		SD	

